

Response
Serial No. 10/015,836

RECEIVED
CENTRAL FAX CENTER
OCT 09 2007

Docket No. AT000068

IN THE CLAIMS:

1. (Previously presented) A recording arrangement (1) for the error-tolerant recording of an information signal (FS) of an information broadcast programmed for recording and identified by a broadcast identification (VPS-PI) and a broadcast start time (SBZ-PI), having

receiving means (4) for receiving the information signal (FS) in which information broadcasts and associated broadcast identifications (VPS-SI) can be transmitted, and having

recording means (6) for recording the received information signal (FS) on a record carrier (8) in a recording mode of the recording arrangement (1), and having

recording control means (11) for evaluating both the broadcast identification (VPS-PI, VPS-SI) of the programmed information broadcast being detected in the information signal (FS) and a recording start time (ABZ) of the programmed information broadcast being reached, which recording start time is reached a lead time interval (VZ) before the broadcast start time (SBZ-PI) of the programmed information broadcast; and for activating the recording mode at the first occurrence of either the broadcast identification or the recording start time.

2. (Original) A recording arrangement (1) as claimed in claim 1, in which the end of the programmed information broadcast is defined by a broadcast end time (SEZ-PI) and in which the recording control means (6) are adapted to deactivate the recording mode when both the absence of the broadcast identification (VPS-PI, VPS-SI) of the programmed information broadcast is detected and a recording end time (AEZ) of the programmed information broadcast is reached, which recording end time is reached a trailing time interval (NZD) after the broadcast end time (SEZ-PI) of the programmed information broadcast.

3. (Original) A recording arrangement (1) as claimed in claim 1, in which marking means (11) are provided, which marking means are adapted, in the recording mode of the recording arrangement (1), to store marking information (MI) defining the current

Response
Serial No. 10/015,836

Docket No. AT000068

recording position (API) on the record carrier (8) when the broadcast identification (VPS-SI) received in the information signal (FS) changes.

4. (Original) A recording arrangement (1) as claimed in claim 1, in which offline analysis means (11) are provided, which analysis means are adapted, after deactivation of the recording mode, to analyze the recorded information signal (WFS) and to mark information signal portions of the recorded information signal (WFS) which have common characteristics with marking information (MI), the characteristics to be analyzed being, for example, a picture frequency, velocity information of objects of the picture content, text information of the picture content, color information of the picture content or sound information of the recorded information signal (WFS).

5. (Original) A recording arrangement (1) as claimed in claim 3 or claim 4, in which the offline analysis means (11) are adapted to define stored marking information (MI) as a reproduction start position (WBP) and/or to define stored marking information (MI) as a reproduction end position (WEP) of the information broadcast recorded in the recording means (6).

6. (Original) A recording arrangement (1) as claimed in claim 1, in which the recording control means (11) are adapted to activate the recording mode when the broadcast identification (VPS-PI) of the information broadcast transmitted before the programmed information broadcast is no longer detected in the sequence of broadcast identifications (VPS-SI) included in the received information signal (FS).

7. (Original) A recording arrangement (1) as claimed in claim 1, in which the recording control means (11) are adapted to deactivate the recording mode when the broadcast identification (VPS-PI) of the information broadcast transmitted after the programmed information broadcast is already detected in the sequence of broadcast identifications (VPS-SI) included in the received information signal (FS).

Response
Serial No. 10/015,836

Docket No. AT000068

8. (Original) A recording arrangement as claimed in claim 1, in which further receiving means for receiving a further information signal are provided, in which further information signal further programmable information broadcasts and associated broadcast identifications can be transmitted.

9. (Original) A recording arrangement (1) as claimed in claim 1, in which recording scheduler means (10, 11, 14) are provided by which an information broadcast to be recorded can be programmed and which are adapted to evaluate electronic program information (PI) received by the receiving means (4), which electronic program information includes both broadcast start times (SBZ) and the expected sequence of broadcast identifications (VPS-PI) of the information broadcasts to be expected in the information signal (FS) to be recorded.

10. (Original) A recording arrangement (1) as claimed in claim 1, in which the record carrier (8) takes the form of a hard disk.

11. (Original) A recording arrangement (1) as claimed in claim 1, in which the recording control means include VPS decoder means (13) for decoding a VPS code which forms the broadcast identification.

12. (Previously presented) A recording method for the error-tolerant recording of an information signal (FS) of an information broadcast programmed for recording and identified by a broadcast identification (VPS-PI) and a broadcast start time (SBZ-PI), in which the following steps are performed:

receiving the information signal (FS) in which information broadcasts and associated broadcast identifications (VPS-SI) can be transmitted;

evaluating both the broadcast identification (VPS-PI, VPS-SI) of the programmed information broadcast being detected in the information signal (FS) and a recording start time (ABZ) of the programmed information broadcast, which recording start time is

Response
Serial No. 10/015,836

Docket No. AT000068

reached a lead time interval (VZ) before the broadcast start time (SBZ-PI) of the programmed information broadcast; and,

recording the received information signal (FS) when a recording mode is active; and,

activating the recording mode at the first occurrence of either the broadcast identification (VPS-PI, VPS-SI) of the programmed information broadcast being detected in the information signal (FS) or a recording start time (ABZ) of the programmed information broadcast being reached.

13. (Original) A recording method as claimed in claim 12, in which the end of the programmed information broadcast is defined by a broadcast end time (SEZ-PI) and in which the recording mode is deactivated when both the absence of the broadcast identification (VPS-PI, VPS-SI) of the programmed information broadcast is detected and a recording end time (AEZ) of the programmed information broadcast is reached, which recording end time is reached a trailing time interval (NZ) after the broadcast end time (SEZ-PI) of the programmed information broadcast.